



MATERIAL SAFETY DATA SHEET

ALPHA-THERM

UN CODE No : NA D.G. CLASS : NA SUBSIDIARY RISK : NONE
HAZCHEM CODE : NA POISONS : 5 MANUFR'S CODE : SHS
TOXIC SUBSTANCES SCHEDULE Not Listed MARINE POLLUTANT : NA

USE :
Proprietary blend of SYNTHETIC POLYMER EMULSIONS, encapsulated micro-spheres, special fillers
Used as a thin film heat insulating, protective and waterproof coating for metal substrates, pipes, roof decks.

PHYSICAL DATA

APPEARANCE : Viscous Liquid PERCENT VOLATILE : 32-35% W/W
SPECIFIC GRAVITY : 1.00 approx FLAMMABILITY LIMITS : LFL 1.1%
FLASH POINT : NA AUTO IGNITION : Not determined
ODOUR : No odor BOILING POINT : > 90 °C

INGREDIENTS

<u>CHEMICAL ENTITY</u>	<u>CAS NO</u>	<u>PROPORTION</u>
Synthetic Polymer Emulsion	Proprietary	55-65
Ester Alcohol	025265-77-4	1.0 max
Titanium Dioxide	013463-67-7	5-10
Other Color Pigments	051274-00-1	3-5
Inert Fillers	014807-96-6	1-2
Encapsulated micro-spheres	Proprietary	Approx 10
Calcium Carbonate	001317-65-3	Approx 15

HEALTH HAZARD INFORMATION

HEALTH EFFECTS

Swallowed May cause nausea. If liquid enters lungs, may cause lung damage.

Eyes May cause slight temporary irritation and soreness

Skin May cause dryness, skin irritation, dermatitis if exposure is repeated, prolonged

Inhaled May cause nausea, headache, irritation of nose, throat irritation.

Chronic No known health hazard

Toxicity Low, from available data. Long term experience of this product type indicates no danger to health when handled under industrial conditions.



FIRST AID

Swallowed If swallowed, drink water immediately. Do not induce vomiting. Seek medical attention.
Eye Flush with plenty of water for 15 minutes. Seek medical attention promptly.
Skin Remove contaminated clothing. Wash skin thoroughly with soap and water for 15 minutes. DO NOT use solvents to remove product from skin. Wash clothing thoroughly before reuse. Consult a physician if irritation persists.
Inhaled Remove to fresh air location. If discomfort persists, seek medical advice.
FA Facilities Provide eye washing facilities

ADVICE TO DOCTOR (EMERGENCY TREATMENT)

Treat symptomatically. The decision whether to induce vomiting or not should be made by an attending physician. If lavage is performed, suggest endo-tracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. No specific antidote. Supportive care. Treatment based on the sound judgment of the attending physician and the individual reactions of the patient.

PRECAUTIONS FOR USE

EXPOSURE LIMITS

WORKPLACE EXPOSURE STANDARD

Component	TWA (8 hr)	ppm	mgm/m3 TLV	ppm	mgm/m3
Butyl Acrylate		10	55	---	---
Styrene Monomers		50	215	100	425
Ammonia		25	18	35	27

ENGINEERING CONTROLS

VENTILATION : General ventilation is usually adequate. Where product is used in an enclosed area, local extraction is recommended. It is not expected that the above Exposure Standards will be exceeded in any use of this product, having regard to the trace amounts of the listed items in the product.

PERSONAL PROTECTION

Eyes Use of chemical splash goggles is recommended
Hands/Feet PVC, rubber or neoprene footwear / gloves are recommended
Respiratory No problems foreseen. A half mask, air-purifying respirator is recommended if and when the airborne concentrations rises to around 10 times of the TWA/TLVs listed in the Exposure Limit Information
Flammability Not flammable under conditions of use.

FLAMMABILITY LIMITS (%)

Lower Explosive Limit Not Applicable
Upper Explosive Limit Not Applicable

SOLUBILITY in H₂O Can be diluted

Although this product does not meet the parameters for flammability, it can burn in the presence of a strong ignition source after water has been removed from the product. Material can splatter at temperatures > 100 °C



SAFE HANDLING INFORMATION

Storage / Transport

This product is NOT classified as a Dangerous Good for the purpose of storage or transportation.
Store in a cool place away from heat and ignition sources. If stored in bulk, then fumes could arise in tank. Observe safe tank entry procedure. Do not store in areas where the maximum temperatures can exceed 50°C. Keep partially used product containers closed. Store away from foodstuffs, clothing. Keep out of reach of children.

Spills

Minor : Absorb to sand, sawdust or an absorbent clay.

Alternatively add calcium or alum to the spill to coagulate solids. Dispose to landfill after drying.

Major : Immediately contain, then pump to a container. Prevent entry to municipal sewers & open water.

Disposal

Separate solids by coagulation or drying. Place in secure container for disposal. Burn in an adequate incinerator or bury to dispose in an approved land-fill in accordance with State and /or Local Government regulations.

FIRE / EXPLOSION

Flammable Limits in Air (% vol)

LEL : None

UEL : None

Extinguishing Media

Any. (For surrounding fire, use appropriate media.)

Fire Fighting

The material can splatter in temperatures > 100 ° C.
The dried polymer is combustible (as plastic).

Additional Hazards

Smoke inhalation from ignition of dried polymer.

Decomposition Products

May yield acrylic monomers on thermal decomposition

Hazardous Polymerization

Will not occur.

Instability

NIL --- Avoid temperatures above 165 ° C.

Toxicological Information

As stated earlier under toxicity data available for this material.

EMERGENCY CONTACTS

Office hours Contact Number

(65)-6546-1181

After hours Contact Number

----as above----

This document is a technical data information sheet. The description of the product and the properties of the product contained in this document is for the sole purpose of identifying the product and describing its properties and does not constitute a specification or a warranty that the product or its properties shall conform to that description; nor is the description of the product and /or its properties a warranty that the goods are suitable for a particular purpose. No warranty either express or implied or statutory is made in this document, except as expressly stated in any sale and purchase agreement entered into between the manufacturer and the buyer. The information given above is based on the most accurate information available at the time of writing and is given in good faith, but is subject to change without notice.